

SPECIFICATION SHEET

DELIGHT

HERRITAGE COLLECTION

HERRINGBONE



OVERVIEW

Wood species	European Oak
Design	Herringbone
Grade	Mill Run
Profile	Tongue and grooved to all sides
Edge Detail	Micro bevelled
Construction	2 Layer Engineered
Backing	Birch plywood
Wear layer	3,5 mm oak (nominal) for 15 mm board 5,5 mm oak (nominal) for 20 mm board

DIMENSIONS

Width	100 mm
Length	500 mm
Pack Size	0.6 m ² for 15mm/0.4m ² for 20 mm

FINISH

Finish	UV oil
Surface	Brushed
Tonal Variation	natural tonal variations
Batch Variation	Not advised to mix batches in one floor area

ENVIRONMENTAL CERTIFICATION

FSC	Chain-of-custody
-----	------------------

INSTALLATION GUIDELINES

Fully Bond	Recomended
------------	------------

TECHNICAL INFORMATION

Moisture Content	8-12% fair and avarage moisture content
Slip Rating	93 PTV (CEN/TS 15676:2007 „Wood flooring – Slip resistance – Pendulum test“)
Formaldehyde Emission	E1 (PN-EN717-1:2006)
Pentachlorophenol Emission	<0,1 mg/kg
Humidity requirents	40-60% relative humidity
Origin	Europe
Janka Hardness Rating	1,010 lbf (4500N)
Reaction to Fire Certification	Cfl-s1 (PN-EN1432:2013)
Thermal Conductivity	15 mm (0,085 m ² *K/W) 20 mm (0,114 m ² *K/W)

WARRANTY

Warranty	25 year structural warranty
Life cycle	Generational if cared for

SHIPMENT INFORMATION

Shipment times	for standard product 7 day service
----------------	------------------------------------

Company Number: 09858736

✉ office@woodconnexions.com


🌐 www.woodconnexions.com

SPECIFICATION SHEET

DELIGHT

HERRITAGE COLLECTION

PLANK



W O O D
CONNEXIONS

OVERVIEW

Wood species	European Oak
Design	Plank
Grade	Character
Profile	Tongue and grooved to all sides
Edge Detail	Micro bevelled
Construction	2 Layer Engineered
Backing	Birch plywood
Wear layer	3,5 mm oak (nominal) for 15 mm board 5,5 mm oak (nominal) for 20 mm board

DIMENSIONS

Width	180 mm
Length	600 - 2300 mm
Pack Size	2.322 m ²

FINISH

Finish	UV oil
Surface	Brushed
Tonal Variation	natural tonal variations
Batch Variation	Not advised to mix batches in one floor area

ENVIROMENTAL CERTIFICATION

FSC	Chain-of-custody
-----	------------------

INSTALLATION GUIDELINES

Fully Bond	Recomended
------------	------------

TECHNICAL INFORMATION

Moisture Content	8-12% fair and avarage moisture content
Slip Rating	93 PTV (CEN/TS 15676:2007 „Wood flooring – Slip resistance – Pendulum test“)
Formaldehyde Emission	E1 (PN-EN717-1:2006)
Pentachlorophenol Emission	<0,1 mg/kg
Humidity requirents	40-60% relative humidity
Origin	Europe
Janka Hardness Rating	1,010 lbf (4500N)
Reaction to Fire Certification	Cfl-s1 (PN-EN1432:2013)
Thermal Conductivity	15 mm (0,085 m ² *K/W) 20 mm (0,114 m ² *K/W)

WARRANTY

Warranty	25 year structural warranty
Life cycle	Generational if cared for

SHIPMENT INFORMATION

Shipment times	for standard product 7 day service
----------------	------------------------------------

Company Number: 09858736

✉ office@woodconnexions.com

🌐 www.woodconnexions.com