


# SPECIFICATION SHEET

# PRALINE

## HERRITAGE COLLECTION

HERRINGBONE



WOOD  
CONNEXIONS

### OVERVIEW

Wood species	European Oak
Design	Herringbone
Grade	Mill Run
Profile	Tongue and grooved to all sides
Edge Detail	Micro bevelled
Construction	2 Layer Engineered
Backing	Birch plywood
Wear layer	3,5 mm oak (nominal) for 15 mm board 5,5 mm oak (nominal) for 20 mm board

### DIMENSIONS

Width	100 mm
Length	500 mm
Pack Size	0.6 m <sup>2</sup> for 15mm/0.4m <sup>2</sup> for 20 mm

### FINISH

Finish	UV oil
Surface	Brushed
Tonal Variation	natural tonal variations
Batch Variation	Not advised to mix batches in one floor area

### ENVIROMENTAL CERTIFICATION

FSC	Chain-of-custody
-----	------------------

### INSTALLATION GUIDELINES

Fully Bond	Recomended
------------	------------

### TECHNICAL INFORMATION

Moisture Content	8-12% fair and avarage moisture content
Slip Rating	93 PTV (CEN/TS 15676:2007 „Wood flooring – Slip resistance – Pendulum test“)
Formaldehyde Emission	E1 (PN-EN717-1:2006)
Pentachlorophenol Emission	<0,1 mg/kg
Humidity requirents	40-60% relative humidity
Origin	Europe
Janka Hardness Rating	1,010 lbf (4500N)
Reaction to Fire Certification	Cfl-s1 (PN-EN1432:2013)
Thermal Conductivity	15 mm (0,085 m <sup>2</sup> *K/W) 20 mm (0,114 m <sup>2</sup> *K/W)

### WARRANTY

Warranty	25 year structural warranty
Life cycle	Generational if cared for

### SHIPMENT INFORMATION

Shipment times	for standard product 7 day service
----------------	------------------------------------

✉ [office@woodconnexions.com](mailto:office@woodconnexions.com)

🌐 [www.woodconnexions.com](http://www.woodconnexions.com)

Company Number: 09858736

# SPECIFICATION SHEET

# PRALINE

## HERRITAGE COLLECTION

PLANK



### OVERVIEW

Wood species	European Oak
Design	Plank
Grade	Character
Profile	Tongue and grooved to all sides
Edge Detail	Micro bevelled
Construction	2 Layer Engineered
Backing	Birch plywood
Wear layer	3,5 mm oak (nominal) for 15 mm board 5,5 mm oak (nominal) for 20 mm board

### DIMENSIONS

Width	180 mm
Length	600 - 2300 mm
Pack Size	2.322 m <sup>2</sup>

### FINISH

Finish	UV oil
Surface	Brushed
Tonal Variation	natural tonal variations
Batch Variation	Not advised to mix batches in one floor area

### ENVIRONMENTAL CERTIFICATION

FSC	Chain-of-custody
-----	------------------

### INSTALLATION GUIDELINES

Fully Bond	Recommended
------------	-------------

### TECHNICAL INFORMATION

Moisture Content	8-12% fair and average moisture content
Slip Rating	93 PTV (CEN/TS 15676:2007 „Wood flooring – Slip resistance – Pendulum test“)
Formaldehyde Emission	E1 (PN-EN717-1:2006)
Pentachlorophenol Emission	<0,1 mg/kg
Humidity requires	40-60% relative humidity
Origin	Europe
Janka Hardness Rating	1,010 lbf (4500N)
Reaction to Fire Certification	Cfl-s1 (PN-EN1432:2013)
Thermal Conductivity	15 mm (0,085 m <sup>2</sup> *K/W) 20 mm (0,114 m <sup>2</sup> *K/W)

### WARRANTY

Warranty	25 year structural warranty
Life cycle	Generational if cared for

### SHIPMENT INFORMATION

Shipment times	for standard product 7 day service
----------------	------------------------------------

Company Number: 09858736

✉ [office@woodconnexions.com](mailto:office@woodconnexions.com)

🌐 [www.woodconnexions.com](http://www.woodconnexions.com)